

# Sms-api.online GET API

## GET Send SMS

```
https://api.sms-api.online/send?token=123456789012345678901234567890&phone=441316080906&senderID=Test&text=Hello%20world
```

Send single SMS

HEADERS

---

### Content-Type

application/json

PARAMS

---

### token

123456789012345678901234567890

### phone

441316080906

### senderID

Test

### text

Hello%20world

BODY raw

---

```
{
  "username": "Des",
  "password": "DesDesDesDes"
}
```

Example Request

```
curl --location --request GET 'https://api.sms-api.online/send?token=123456789012345678901234567890&phone=441316080906&senderID=Test&text=Hello%20world' \
--header 'Content-Type: application/json' \
--data-raw '{
  "username": "Des",
  "password": "DesDesDesDes"
}'
```

GET State

https://api.sms-api.online/state?token=123456789012345678901234567890&states=2641185,5751,5750

Get Delivering status by GET API

HEADERS

---

**Content-Type**

application/json

PARAMS

---

**token**

123456789012345678901234567890

**states**

2641185,5751,5750

BODY raw

---

```
{  
  "username": "Des",  
  "password": "DesDesDesDes"  
}
```

Example Request

```
curl --location --request GET 'https://api.sms-api.online/state?token=123456789012345678901234567890&states=2641185,5751,5750' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "username": "Des",  
  "password": "DesDesDesDes"  
}'
```

# Sms-api.online POST API

## POST Authorization

https://restapi.sms-api.online/v1/authorize

Authorization via login and pass

HEADERS

### Content-Type

application/json

BODY raw

```
{
  "username": "Sms-api.onlineLogin",
  "password": "pass"
}
```

Example Request

Authorization

```
curl --location --request POST 'https://restapi.sms-api.online/v1/authorize' \
--header 'Content-Type: application/json' \
--data-raw '{
  "username": "Sms-api.onlineLogin",
  "password": "pass"
}'
```

## POST Access token

https://restapi.sms-api.online/v1/accesstoken

Ask access token via Authorization code (which we got from Authorization API)

HEADERS

### Content-Type

application/json

BODY raw

```
{
  "authorization_code": "b2cdedb10785e36928727a1ffb73aa4e"
}
```

Example Request

```
curl --location --request POST 'https://restapi.sms-api.online/v1/accesstoken' \
```

```
--header 'Content-Type: application/json' \  
--data-raw '{  
  "authorization_code": "b2cdedb10785e36928727a1ffb73aa4e"  
}'
```

## GET Me

https://restapi.sms-api.online/v1/me

Asking information about account via Token (which we got from Access token API)

HEADERS

---

### X-Access-Token

12345678901234567890123456789

Example Request

Me

```
curl --location --request GET 'https://restapi.sms-api.online/v1/me' \  
--header 'X-Access-Token: 12345678901234567890123456789'
```

## POST Send single sms

https://restapi.sms-api.online/v1/send

Send SMS using access token. By params:

- number - list of the phone numbers
- senderID - sender ID from which your sms will fgo
- text - content of the message
- type - type of message (SMS, HLR, WAPPUSH, FLASHSMS)
- beginDate - plan date where message will go
- beginTime - plan time where message will go
- lifetime - period how long message will live
- delivery - enable of automatical back of DLR reports

WARNING: Not more then 200 messages by one package

HEADERS

---

### X-Access-Token

efe36eb9de336ef133f0cb837a6afed7

### Content-Type

application/json

BODY raw

---

```
[ {  
  "number": ["380662225588"],
```

```

    "senderID":"Sms-api.online",
    "text":"Hello\nHowdfdfsdfgdgsf авапавпвап авп выпыывапыв аывап ывап ывапывап
вапыывапывапывап вапвапвапвапав are you?",
    "type":"sms",
    "beginDate":"2018-12-31",
    "beginTime":"11:00",
    "lifetime":555,
    "delivery":false
  },
  {
    "number":["380662225582","79225558877"],
    "senderID":"Sms-api.online",
    "text":"Hello\nHow are you?",
    "type":"sms",
    "beginDate":"2018-12-31",
    "beginTime":"11:00",
    "lifetime":555,
    "delivery":false
  }
}

```

### Example Request

#### Send single sms

```

curl --location --request POST 'https://restapi.sms-api.online/v1/send' \
--header 'X-Access-Token: efe36eb9de336ef133f0cb837a6afed7' \
--header 'Content-Type: application/json' \
--data-raw '{
  "number":["380662225588"],
  "senderID":"Sms-api.online",
  "text":"Hello\nHowdfdfsdfgdgsf авапавпвап авп выпыывапыв аывап ывап
ывапыывапвапвапыывапывап вапвапвапвапав are you?",
  "type":"sms",
  "beginDate":"2018-12-31",
  "beginTime":"11:00",
  "lifetime":555,
  "delivery":false
},
{
  "number":["380662225582","79225558877"],
  "senderID":"Sms-api.online",
  "text":"Hello\nHow are you?",
  "type":"sms",
  "beginDate":"2018-12-31",
  "beginTime":"11:00",
  "lifetime":555,
  "delivery":false
}'

```

### POST State

<http://restapi.sms-api.online/v1/state>

Get DLR status using access token. By params:

- states - list of IDs for checking

WARNING: Not more then 200 IDs by one package

HEADERS

---

**X-Access-Token**

d1b43b2703de49cf5c983ea5a1d77dc3

### Content-Type

application/json

BODY raw

```
{
  "states": ["5799"]
}
```

Example Request

State

```
curl --location --request POST 'http://restapi.sms-api.online/v1/state' \
--header 'X-Access-Token: d1b43b2703de49cf5c983ea5a1d77dc3' \
--header 'Content-Type: application/json' \
--data-raw '{
  "states": ["5799"]
}'
```

## POST Group list

https://restapi.sms-api.online/v1/group

Group list of user's account Fields:

- id\_group - group ID
- limit - limit of list data (not more 100)
- offset - pages of list

HEADERS

### X-Access-Token

87ee8c1b4119d737d2975d381c44a369

### Content-Type

application/json

BODY raw

```
{
  "id_group":12,
  "limit":5,
  "offset":1
}
```

Example Request

```
curl --location --request POST 'https://restapi.sms-api.online/v1/group' \
```

```
--header 'X-Access-Token: 87ee8c1b4119d737d2975d381c44a369' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
    "id_group":12,  
    "limit":5,  
    "offset":1  
}'
```

## POST Create group

https://restapi.sms-api.online/v1/group-create

Creating group of numbers for bulk sending Fields:

- name\_group - name of the group
- time\_birth - congratulations time
- originator\_birth - SenderID for sms of congratulations
- text\_birth - text of congratulations
- on\_birth - mark of enabling congratulations

### HEADERS

#### X-Access-Token

87ee8c1b4119d737d2975d381c44a369

#### Content-Type

application/json

#### BODY raw

```
{  
  "name_group": "bigRest",  
  "time_birth": "23:22",  
  "originator_birth": "aafd",  
  "text_birth": "ss#middssasale_name#s",  
  "on_birth": false  
}
```

### Example Request

```
curl --location --request POST 'https://restapi.sms-api.online/v1/group-create' \  
--header 'X-Access-Token: 87ee8c1b4119d737d2975d381c44a369' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "name_group": "bigRest",  
  "time_birth": "23:22",  
  "originator_birth": "aafd",  
  "text_birth": "ss#middssasale_name#s",  
  "on_birth": false  
}'
```

## POST Delete group

https://restapi.sms-api.online/v1/group-delete

Deleting groups of numbers of user Fields:

- id\_group - a list of groups for deleting

HEADERS

---

**X-Access-Token**

87ee8c1b4119d737d2975d381c44a369

**Content-Type**

application/json

BODY raw

```
{
  "id_group": [1,2,3,4,5,6,7,8,9,10,11,12]
}
```

Example Request

Delete group

```
curl --location --request POST 'https://restapi.sms-api.online/v1/group-delete' \
--header 'X-Access-Token: 87ee8c1b4119d737d2975d381c44a369' \
--header 'Content-Type: application/json' \
--data-raw '{
  "id_group": [1,2,3,4,5,6,7,8,9,10,11,12]
}'
```

## POST Add numbers in group

https://restapi.sms-api.online/v1/group-number-add

Adding mobile numbers in group for bulk sending. All numbers should be in international format Fields:

- id\_group - group ID where we should add numbers
- numbers - array of data
- number - mobile number
- name - name of mobile holder (not required)
- surname - surname of mobile holder (not required)
- patronymic - patronymic of mobile holder (not required)
- date\_birth - birthday of mobile holder (not required)
- male - male of mobile holder (not required)
- addition\_1 - addinital info (not required)
- addition\_2 - addinital info (not required)

HEADERS

---

**X-Access-Token**

87ee8c1b4119d737d2975d381c44a369



## Content-Type

application/json

BODY raw

```
{
  "id_group": 13,
  "numbers": [{
    "number": 380660977249,
    "name": "Iogan",
    "surname": "Bah",
    "patronymic": "Sebastian",
    "date_birth": "2018-12-31",
    "male": "m",
    "addition_1": "tralivali",
    "addition_2": "tralivali2"
  }],
  {
    "number": 380660977252,
    "name": "Iogan2",
    "surname": "Bah2",
    "patronymic": "Sebastian2",
    "date_birth": "2018-12-31",
    "male": "l",
    "addition_1": "tralivali2",
    "addition_2": "tralivali23"
  },
  {
    "number": 380660977249,
    "name": "Vasua",
    "surname": "asdas",
    "patronymic": "stroke",
    "date_birth": "2018-12-30",
    "male": "m",
    "addition_1": "www",
    "addition_2": "wwdqww"
  },
  {
    "number": 380660277249,
    "name": "Vasua",
    "surname": "asdas",
    "patronymic": "stroke",
    "date_birth": "2018-12-30",
    "male": "m",
    "addition_1": "www",
    "addition_2": "wwdqww"
  },
  {
    "number": 380660977229,
    "name": "Vasua",
    "surname": "asdas",
    "patronymic": "stroke",
    "date_birth": "2018-12-30",
    "male": "m",
    "addition_1": "www",
    "addition_2": "wwdqww"
  }
}]
}
```

Example Request

```
curl --location --request POST 'https://restapi.sms-api.online/v1/group-number-add' \
```

```

--header 'X-Access-Token: 87ee8c1b4119d737d2975d381c44a369' \
--header 'Content-Type: application/json' \
--data-raw '{
  "id_group": 13,
  "numbers": [{
    "number": 380660977249,
    "name": "Iogan",
    "surname": "Bah",
    "patronymic": "Sebastian",
    "date_birth": "2018-12-31",
    "male": "m",
    "addition_1": "tralivali",
    "addition_2": "tralivali2"
  }],
  {
    "number": 380660977252,
    "name": "Iogan2",
    "surname": "Bah2",
    "patronymic": "Sebastian2",
    "date_birth": "2018-12-31",
    "male": "l",
    "addition_1": "tralivali2",
    "addition_2": "tralivali23"
  },
  {
    "number": 380660977249,
    "name": "Vasua",
    "surname": "asdas",
    "patronymic": "stroke",
    "date_birth": "2018-12-30",
    "male": "m",
    "addition_1": "www",
    "addition_2": "wwdqww"
  },
  {
    "number": 380660277249,
    "name": "Vasua",
    "surname": "asdas",
    "patronymic": "stroke",
    "date_birth": "2018-12-30",
    "male": "m",
    "addition_1": "www",
    "addition_2": "wwdqww"
  },
  {
    "number": 380660977229,
    "name": "Vasua",
    "surname": "asdas",
    "patronymic": "stroke",
    "date_birth": "2018-12-30",
    "male": "m",
    "addition_1": "www",
    "addition_2": "wwdqww"
  }
}]
}'

```

## POST Search numbers in group

<https://restapi.sms-api.online/v1/group-number-search>

Looking for numbers in selected group Fields:

- id\_group - group id
- numbers - list of mobile numbers for search

## HEADERS

---

### X-Access-Token

87ee8c1b4119d737d2975d381c44a369

### Content-Type

application/json

BODY raw

```
{
  "id_group": 13,
  "numbers": [380660977249, 380660977252, 380660977249, 380660277249, 380660977229,
  17133010164]
}
```

## Example Request

```
curl --location --request POST 'https://restapi.sms-api.online/v1/group-number-search' \
--header 'X-Access-Token: 87ee8c1b4119d737d2975d381c44a369' \
--header 'Content-Type: application/json' \
--data-raw '{
  "id_group": 13,
  "numbers": [380660977249, 380660977252, 380660977249, 380660277249, 380660977229, 17133010164]
}'
```

## POST Delete numbers from group

<https://restapi.sms-api.online/v1/group-number-delete>

Delete a list on numbers from selected group Fields:

- id\_group - group ID
- numbers - list of numbers for deleting

## HEADERS

---

### X-Access-Token

87ee8c1b4119d737d2975d381c44a369

### Content-Type

application/json

BODY raw

```
{
  "id_group": 13,
  "numbers": [380660977249, 380660977252, 380665558877, 17133010164, 15742201221]
}
```

```
}
```

#### Example Request

Delete numbers from group

```
curl --location --request POST 'https://restapi.sms-api.online/v1/group-number-delete' \  
--header 'X-Access-Token: 87ee8c1b4119d737d2975d381c44a369' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "id_group": 13,  
  "numbers": [380660977249, 380660977252, 380665558877, 17133010164, 15742201221]  
}'
```

## POST Bulk sending sms

<https://restapi.sms-api.online/v1/send-bulk>

Send bulk sms from selected groups Fields:

- senderID - sender name of sms
- text - content of sms
- dateStart - date of begin of sending (not required)
- timeStart - time of start sending (not required)
- timeStop - time of stop sending (not required)
- phone - extra number for sending (not required)
- id\_group - list of groups for sending
- id\_group\_excluded - list of groups which numbers should not receive sms (not required)

#### HEADERS

---

##### **X-Access-Token**

87ee8c1b4119d737d2975d381c44a369

##### **Content-Type**

application/json

#### BODY raw

```
{  
  "senderID": "Vasyaa",  
  "text": "Hello #first_name#, We send sms to #number#",  
  "dateStart": "2019-12-14",  
  "timeStart": "22:30",  
  "timeStop": "22:30",  
  "phone": "380662225588",  
  "id_group": [17],  
  "id_group_excluded": [24, 26]  
}
```

#### Example Request

Bulk sending sms

```
curl --location --request POST 'https://restapi.sms-api.online/v1/send-bulk' \  
--header 'X-Access-Token: 87ee8c1b4119d737d2975d381c44a369' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "senderID":"Vasyaa",  
  "text":"Hello #first_name#, We send sms to #number#",  
  "dateStart":"2019-12-14",  
  "timeStart":"22:30",  
  "timeStop":"22:30",  
  "phone":"380662225588",  
  "id_group":[17],  
  "id_group_excluded":[24,26]  
}'
```

## POST Add numbers in black list

<https://restapi.sms-api.online/v1/black-list-add>

Add a list numbers at black list

HEADERS

### X-Access-Token

87ee8c1b4119d737d2975d381c44a369

### Content-Type

application/json

BODY raw

```
{  
  "numbers": [380660977249, 380660977252, 380660977249, 17884567895]  
}
```

Example Request

```
curl --location --request POST 'https://restapi.sms-api.online/v1/black-list-add' \  
--header 'X-Access-Token: 87ee8c1b4119d737d2975d381c44a369' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "numbers": [380660977249, 380660977252, 380660977249, 17884567895]  
}'
```

## POST Search numbers at black list

<https://restapi.sms-api.online/v1/black-list-search>

Looking for numbers in black list

HEADERS

### X-Access-Token

87ee8c1b4119d737d2975d381c44a369

**Content-Type**

application/json

BODY raw

```
{  
  "numbers": [380660977249, 380660977252, 380660977249, 17884567895]  
}
```

**Example Request**

```
curl --location --request POST 'https://restapi.sms-api.online/v1/black-list-search'  
\ --header 'X-Access-Token: 87ee8c1b4119d737d2975d381c44a369' \  
\ --header 'Content-Type: application/json' \  
\ --data-raw '{  
  "numbers": [380660977249, 380660977252, 380660977249, 17884567895]  
}'
```

**POST** Delete numbers from black list

https://restapi.sms-api.online/v1/black-list-delete

Deleting numbers from black list

HEADERS

**X-Access-Token**

87ee8c1b4119d737d2975d381c44a369

**Content-Type**

application/json

BODY raw

```
{  
  "numbers": [380660977252]  
}
```